TCI EUROPE N.V.

G

SAFETY DATA SHEET

According to 1907/2006/EC, Article 31

Revision number: 1 Revision date: 08/01/2			
SECTION 1: Identification of th	e substance/mixture and of the company/undertaking		
1.1 Product identifiers			
Product name:	Hexane [for Liquid Paraffin Test]		
Product code:	H0405		
1.2 Relevant identified uses of the Identified uses:	substance or mixture and uses advised against Reagents.		
1.3 Details of the supplier of the sa	fety data sheet		
Supplier: TCI EUROPE N.V.			
Boerenveldseweg 6			
Haven 1063			
B-2070 Zwijndrecht			
Telephone: +32(0)3 735 0	7 00		
E-mail: sales-eu@tcichem			
1.4 Emergency telephone number:	+32(0)70 245 245		
SECTION 2: Hazards identifica			
2.1 Classification of the substance			
Flammable liquids	Category 2		
Skin corrosion/irritation	Category 2		
Reproductive toxicity	Category 2		
Specific target organ toxicity -			
	Repeated exposure [Category 2] Organs		
Aspiration hazard	Category 1		
-			
Long-term aquatic hazard 2.2 Label elements	Category 2		
Long-term aquatic hazard	Category 2		
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols	Category 2		
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols	Category 2		
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols	Category 2		
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols	Category 2 Category 2 Danger H225-Highly flammable liquid and vapour.		
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols	Category 2 Category 2 Danger H225-Highly flammable liquid and vapour. H315-Causes skin irritation. H361f-Suspected of damaging fertility. H373-May cause damage to organs through prolonged or repeated exposure	e.	
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols	Category 2 Category 2 Danger H225-Highly flammable liquid and vapour. H315-Causes skin irritation. H361f-Suspected of damaging fertility. H373-May cause damage to organs through prolonged or repeated exposure H336-May cause drowsiness or dizziness.	e.	
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols	Category 2 Category 2 Danger H225-Highly flammable liquid and vapour. H315-Causes skin irritation. H361f-Suspected of damaging fertility. H373-May cause damage to organs through prolonged or repeated exposure H336-May cause drowsiness or dizziness. H304-May be fatal if swallowed and enters airways.	e.	
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols Signal word Hazard statements	Category 2 Category 2 Danger H225-Highly flammable liquid and vapour. H315-Causes skin irritation. H361f-Suspected of damaging fertility. H373-May cause damage to organs through prolonged or repeated exposure H336-May cause drowsiness or dizziness. H304-May be fatal if swallowed and enters airways. H411-Toxic to aquatic life with long lasting effects.	e.	
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols	Category 2	e.	
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols Signal word Hazard statements	Category 2		
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols Signal word Hazard statements	Category 2		
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols Signal word Hazard statements	Category 2	or doctor. Do NOT induce	
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols Signal word Hazard statements	Category 2 Very Category 2 Danger H225-Highly flammable liquid and vapour. H315-Causes skin irritation. H361f-Suspected of damaging fertility. H373-May cause damage to organs through prolonged or repeated exposure H336-May cause damage to organs through prolonged or repeated exposure H336-May cause damage to organs through prolonged or repeated exposure H336-May cause damage to organs through prolonged or repeated exposure H336-May cause drowsiness or dizziness. H304-May be fatal if swallowed and enters airways. H411-Toxic to aquatic life with long lasting effects. P260-Do not breathe mist, vapours or spray. P280-Wear protective gloves, protective clothing, face protection. P301+P310+P331-IF SWALLOWED: Immediately call a POISON CENTER of womiting. P302+P352+P332+P313+P362+P364-IF ON SKIN: Wash with plenty of wat Get medical advice or attention. Take off contaminated clothing and wash it	or doctor. Do NOT induce ter. If skin irritation occurs: before reuse.	
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols Signal word Hazard statements	Category 2 Very Category 2 Danger H225-Highly flammable liquid and vapour. H315-Causes skin irritation. H361f-Suspected of damaging fertility. H373-May cause damage to organs through prolonged or repeated exposure H336-May cause damage to organs through prolonged or repeated exposure H336-May cause damage to organs through prolonged or repeated exposure H336-May cause drowsiness or dizziness. H304-May be fatal if swallowed and enters airways. H411-Toxic to aquatic life with long lasting effects. P260-D0 not breathe mist, vapours or spray. P280-Wear protective gloves, protective clothing, face protection. P301+P310+P331-IF SWALLOWED: Immediately call a POISON CENTER or vomiting. P302+P352+P332+P313+P362+P364-IF ON SKIN: Wash with plenty of wat Get medical advice or attention. Take off contaminated clothing and wash it P304+P340+P312-IF INHALED: Remove person to fresh air and keep comfo	or doctor. Do NOT induce ter. If skin irritation occurs: before reuse.	
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols Signal word Hazard statements	Category 2 Very Category 2 Danger H225-Highly flammable liquid and vapour. H315-Causes skin irritation. H315-Causes skin irritation. H361f-Suspected of damaging fertility. H373-May cause damage to organs through prolonged or repeated exposure H304-May be fatal if swallowed and enters airways. H411-Toxic to aquatic life with long lasting effects. P260-Do not breathe mist, vapours or spray. P280-Wear protective gloves, protective clothing, face protection. P301+P310+P331-IF SWALLOWED: Immediately call a POISON CENTER or vomiting. P302+P352+P332+P313+P362+P364-IF ON SKIN: Wash with plenty of watt Get medical advice or attention. Take off contaminated clothing and wash it P304+P340+P312-IF INHALED: Remove person to fresh air and keep comford POISON CENTER or doctor if you feel unwell.	or doctor. Do NOT induce ter. If skin irritation occurs: before reuse.	
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols Signal word Hazard statements Precautionary statements	Category 2 Very Category 2 Danger H225-Highly flammable liquid and vapour. H315-Causes skin irritation. H361f-Suspected of damaging fertility. H373-May cause damage to organs through prolonged or repeated exposure H336-May cause damage to organs through prolonged or repeated exposure H336-May cause damage to organs through prolonged or repeated exposure H336-May cause drowsiness or dizziness. H304-May be fatal if swallowed and enters airways. H411-Toxic to aquatic life with long lasting effects. P260-D0 not breathe mist, vapours or spray. P280-Wear protective gloves, protective clothing, face protection. P301+P310+P331-IF SWALLOWED: Immediately call a POISON CENTER or vomiting. P302+P352+P332+P313+P362+P364-IF ON SKIN: Wash with plenty of wat Get medical advice or attention. Take off contaminated clothing and wash it P304+P340+P312-IF INHALED: Remove person to fresh air and keep comfo	or doctor. Do NOT induce ter. If skin irritation occurs: before reuse.	
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols Signal word Hazard statements Precautionary statements 2.3 Other hazards	Category 2	or doctor. Do NOT induce ter. If skin irritation occurs: before reuse.	
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols Signal word Hazard statements Precautionary statements 2.3 Other hazards Results of PBT and vPvB assess	Category 2	or doctor. Do NOT induce ter. If skin irritation occurs: before reuse.	
Long-term aquatic hazard 2.2 Label elements Pictograms or hazard symbols Signal word Hazard statements Precautionary statements 2.3 Other hazards	Category 2	or doctor. Do NOT induce ter. If skin irritation occurs: before reuse.	

H0405

SECTION 3: Composition/information on ingredients

3.1 Substances	
Components:	Hexane [for Liquid Paraffin Test]
Percent:	>96.0%(GC)
CAS RN:	110-54-3
EC-No:	203-777-6
Chemical Formula:	C6H14

SECTION 4: First aid measures	
4.1 Description of first aid measures	
Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention.
Skin contact:	Remove/Take off immediately all contaminated clothing. Gently wash with plenty of soap and water. Get medical advice/attention.
Eye contact:	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Get medical advice/attention.
Ingestion:	Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting.
Protection of first-aiders:	A rescuer should wear personal protective equipment, such as rubber gloves and air-tight goggles.

4.2 Most important symptoms and effects, both acute and delayed No data available

4.3 Indication of any immediate medical attention and special treatment needed No data available

SECTION 5: Firefighting measures		
5.1 Extinguishing media Suitable extinguishing media:	Dry chemical, foam, carbon dioxide.	
Unsuitable extinguishing media:	Water (It may scatter and spread fire.)	
5.2 Special hazards arising from the substance or mixture	Carbon dioxide, Carbon monoxide	
5.3 Advice for firefighters	Fire-extinguishing work is done from the windward and the suitable fire-extinguishing method according to the surrounding situation is used. Uninvolved persons should evacuate to a safe place. In case of fire in the surroundings: Keep containers cool by spraying with water. Eliminate all ignition sources if safe to do so. When extinguishing fire, be sure to wear personal protective equipment	
SECTION 6: Accidental release mea	asures	
6.1 Personal precautions, protective equipment and emergency procedures	Use extra personal protective equipment (self-contained breathing apparatus). Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Entry to non-involved personnel should be controlled around the leakage area by roping off, etc	
6.2 Environmental precautions	Prevent product from entering drains	
6.3 Methods and materials for containment and cleaning up	Absorb spilled material in dry sand or inert absorbent before recovering it into an airtight container. In case of large amount of spillage, contain a spill by bunding. Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations. Remove all sources of ignition. Fire-extinguishing devices should be prepared in case of a fire. Use spark-proof tools and explosion-proof equipment.	
6.4 Reference to other sections	For disposal see section 13.	
SECTION 7: Handling and storage		
7.1 Precautions for safe handling	Handling is performed in a well ventilated place. Wear suitable protective equipment. Prevent generation of vapour or mist. Keep away from heat/sparks/open flame/hot surfacesNo smoking. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Wash hands and face thoroughly after handling. Use a closed system if possible. Use a ventilation, local exhaust if vapour or aerosol will be generated. Avoid all contact!	
7.2 Conditions for safe storage, including any incompatibilities	Keep container tightly closed. Store in a cool, dark and well-ventilated place. Store under inert gas. Protect from moisture. Store locked up. Store away from incompatible materials such as oxidizing agents. Hygroscopic	
7.3 Specific end use(s)	No further relevant information available.	

H0405

SECTION 8: Exposure controls/personal protection		
8.1 Control parameters		
ACGIH TLV(TWA):	50 ppm (skin)	
OSHA PEL(TWA):	500 ppm	
JSOH OELs(TWA):	40 ppm (skin)	
8.2 Exposure controls	Install a closed system or local exhaust. Also install safety shower and eye bath.	
Respiratory protection:	Half or full facepiece respirator, self-contained breathing apparatus(SCBA), supplied air respirator, etc. Use respirators approved under appropriate government standards and follow local and national regulations.	
Hand protection:	Impervious gloves.	
Eye protection:	Safety goggles. A face-shield, if the situation requires.	
Skin and body protection:	Impervious protective clothing. Protective boots, if the situation requires.	

9.1 Information on basic physical and c	hemical properties
Physical state (20°C):	Liquid
Form:	Clear
Colour:	Colorless - Almost colorless
Odour:	Gasoline-like
Odour threshold:	130 ppm
pH:	No data available
Melting point/freezing point:	-95°C
Boiling point/range:	68°C
Flash point:	-22°C
Evaporation rate(Butyl Acetate=1):	No data available
Flammability(solid, gas):	No data available
Flammability or explosive limits:	
Lower:	1.1%
Upper:	7.5%
Vapour pressure:	17kPa/20°C
Vapour density:	3.0
Relative density:	0.66
Solubility(ies):	
[Water]	Insoluble (0.013g/L, 20°C)
[Other solvents]	
Misciple:	Ether, Alcohols, Chloroform
Soluble:	Acetone
Partition coefficient:	3.9
n-octanol/water:	
Autoignition temperature:	225°C
Decomposition temperature:	No data available
Dynamic Viscosity:	0.25mPa·s (40°C)
Kinematic viscosity:	No data available
9.2 Other safety information	No data available
SECTION 10: Stability and reactivit	у
10.1 Reactivity	No data available

10.1 Reactivity	No data available	
10.2 Chemical stability	Stable under proper conditions.	
10.3 Possibility of hazardous reactions	No special reactivity has been reported.	
10.4 Conditions to avoid	Spark, Open flame, Static discharge	
10.5 Incompatible materials	Oxidizing agents	

10.6 Hazardous decomposition products Carbon dioxide, Carbon monoxide

SECTION 11: Toxicological information

11.1 Information on toxicological effects		
Acute Toxicity:	orl-rat LD50:15840 mg/kg	
	ihl-rat LC50:48000 ppm/4H	
	ihl-hmn TCLo:190 ppm/8W	
Skin corrosion/irritation:	No data available	
Serious eye damage/irritation:	eye-rbt 10 mg MLD	
Respiratory or skin sensitization:	No data available	
Germ cell mutagenicity:	cyt-ham-fbr 500 mg/L	
	cyt-rat-scu 7.5 mL/kg/12W-I	
Carcinogenicity:	ihl-rat TCLo:1000 ppm/4H/59W-I	
	ihl-mus TCLo:9018 ppm/6H/2Y-I	
IARC =	No data available	
NTP =	No data available	
Reproductive toxicity:	ihl-mus TCLo:200 ppm (6-17D preg)	
	ihl-rat TCLo:1000 ppm/6H (8-16D preg)	
STOT-single exposure:	No data available	
STOT-repeated exposure:	No data available	
Aspiration hazard:	No data available	
RTECS Number:	MN9275000	

SECTION 12: Ecological informatic	n	
12.1 Toxicity		
Fish:	96h LC50:2.5 mg/L (Pimephales promelas) 48h LC50:>1000 mg/L (Oryzias latipes)	
Crustacea:	48h EC50:3.9 mg/L (Daphnia magna)	
Algae:	No data available	
12.2 Persistence and degradability	100 % (by BOD) , 100 % (by GC)	
12.3 Bioaccumulative potential	No data available	
12.4 Mobility in soil		
Log Pow:	3.9	
Soil adsorption (Koc):	No data available	
Henry's Law (PaM ³ /mol):	No data available	
12.5 Results of PBT and vPvB assessm	ent	
PBT:	Not applicable	
vPvB:	Not applicable	
12.6 Other adverse effects	No data available	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recycle to process, if possible. Consult your local regional authorities. You may be able to burn in a chemical incinerator equipped with an afterburner and scrubber system but exert extra care in igniting as this material is highly flammable. Observe all federal, state and local regulations when disposing of the substance

SECTION 14: Transport informati	on	
14.1 UN number	1208	
14.2 UN proper shipping name		
ADR/RID	Hexanes	
IMDG/IMO	Hexanes	
ICAO/IATA	Hexanes	
14.3 Transport hazard class(es)		
ADR/RID	3: Flammable liquid	
IMDG/IMO	3: Flammable liquid	
ΙCAO/ΙΑΤΑ	3: Flammable liquid	
14.4 Packaging group		
ADR/RID	П	
IMDG/IMO	П	
ΙCAO/ΙΑΤΑ	II	
14.5 Environmental hazards		
Marine pollutant	-	
14.6 Special precautions for user	No data available	
SECTION 15: Regulatory informa	tion	
15.1 Safety, health and environmenta		
Water Hazard Classes (WGK) :		Class 2 - Hazard to waters
Substance of Very High Concern (SVHC) according to the REACH Regulations (EC) No.1907/2006		Not listed
15.2 Chemical safety assessment		A chemical safety assessment has not been carried out.
SECTION 16: Other information		
Prepared by: Issue date:	TCI EUROPE N.V. 08/01/2022	

This SDS was prepared sincerely on the basis of the information we could obtained, however, any warranty shall not be given regarding the data contained and the assessment of hazards and toxicity. Prior to use, please investigate not only the hazards and toxicity information but also the laws and regulations of the organization, area and country where the products are to be used, which shall be given the first priority. The products are supposed to be used promptly after purchase in consideration of safety. Some new information or amendments may be added afterwards. If the products are to be used far behind the expected time of use or you have any questions, please feel free to contact us. The stated cautions are for normal handling only. In case of special handling, sufficient care should be taken, in addition to the safety measures suitable for the situation. All chemical products should be treated with the recognition of "having unknown hazards and toxicity", which differ greatly depending on the conditions and handling when in use and/or the conditions and duration of storage. The products must be handled only by those who are familiar with specialized knowledge and have experience or under the guidance of those specialists throughout use from opening to storage and disposal. Safe usage conditions shall be set up on each user's own responsibility.

End of Safety Data Sheet